

ITALUB ABF DOT 4

Fluid for braking systems

Product Description:

ABF DOT4 is a mixture of polyglycols and alkyl esters inhibited suitability for use in braking systems of cars, trucks, buses and motorcycles, with the exception of hydraulic systems with mineral oils (eg.: Citroen). Compatible with all brake fluids complying with its specification unless stated otherwise given by the vehicle manufacturer. The contamination of ABF DOT 4 with petroleum products, water or other liquids can cause failure of the braking circuit.

Features and Benefits:

- High boiling point: it can be used without forming within the fluid, dangerous vapor bubbles.
- anticorrosive power to all the components of hydraulic braking systems.
- Low melting temperature.

Specifications and Approval:

Exceeds requirements: FMVSS 116 DOT 4, SAE J 1704, ISO 4925 Class 4, CUNA NC 956 DOT4

Typical properties: ITALUB ABF DOT 4

Appearance	Clear
Color	Amber
Solubility	Partially soluble in water, soluble in ethyl alcohol
Boiling Point, °C	165
Boiling Point (RPB), °C	1./
Flash Point, °C, ASTM D-92	-56
Density @ 20°C, Kg/l, ASTM D-1298	1000
Н	7,8

Health and Safety:

The data related to health, safety and environmental protection are provided in the material safety data sheets.

The above figures are those relating to normal manufacturing tolerances and do not constitute a specification.

ABF DOT 4 Date Created: 18/01/2013 Last Edit: 17/05/2019

This data sheet and the information it contains is believed to be correct with specific reference to the date of printing. The accuracy or completeness of the data and information contained in this publication are not binding in any way the responsibility of the company. The user has the obligation to evaluate and use products safely and in accordance with all applicable laws and regulations currently in force. No statement made in this publication shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a license.