



ITALUB ATF V

Synthetic Fluid ATF for Mercon V

Product Description:

ATF for Mercon V is formulated with premium baseoils combined with advanced additive technology to meet the challenging demands of an automatic transmission environment. Is designed to provide better heat resistance, cold flow capabilities, and transmission shutter resistance than conventional ATFs.

Features and Benefits:

Excellent low temperature fluidity
Provide outstanding resistance to oil breakdown and deposits
Minimizing sludge and varnish deposits
Protect transmission seal materials

Specifications and Approval:

Exceeds requirements: **Ford MERCON V, Allison C-4, Dexron III, Dexron II**

Typical properties:

ITALUB ATF Mercon V

Viscosity ASTM D-445	
cSt @ 40°C	32,4 – 36,5
cSt @ 100°C	6,9 – 7,4
Viscosity Index ASTM D-2270	637,
Pour Point, °C, ASTM D-97	()4
Flash Point, °C, ASTM D-92	800,
Density @ 15°C, Kg/l, ASTM D-1298	≥0,850
Brookfield a -40°C, mPa*s, ASTM D-2983	10.000

Health and Safety:

The data related to health, safety and environmental protection are provided in the material safety data sheets.

The above figures are those relating to normal manufacturing tolerances and do not constitute a specification.

ATF Mercon V Date Created: 18/01/2013 Last Edit: 17/05/2019

This data sheet and the information it contains is believed to be correct with specific reference to the date of printing. The accuracy or completeness of the data and information contained in this publication are not binding in any way the responsibility of the company. The user has the obligation to evaluate and use products safely and in accordance with all applicable laws and regulations currently in force. No statement made in this publication shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a license.