



**LHM**

**Mineral hydraulic fluid**

### Product Description:

LHM is a mineral hydraulic fluid formulated for specific use in Citroen hydraulic circuits.

And 'suitable for use in hydraulic suspension systems, brakes and hydroguide of Citroen vehicles. It 'also indicated for use in vehicles that require fluids of this kind.

Warning LHM is not miscible with other brake fluids such as DOT 3 and DOT 4.

### Features and Benefits:

- Great resistance to oxidation.
- Anticorrosive power.
- Anti-wear properties.
- Perfect compatibility with seals.

### Specifications and Approval:

Exceeds requirements: **PSA-B 712710**

### Typical properties:

**LHM**

Viscosity ASTM D-445

cSt @ 40°C	17,2 – 19,1
------------	-------------

cSt @ 100°C	5,5 – 6,5
-------------	-----------

Viscosity Index ASTM D-2270	270 – 285
-----------------------------	-----------

Pour Point, °C, ASTM D-97	*02
---------------------------	-----

Flash Point, °C, ASTM D-92	460
----------------------------	-----

Density @ 15°C, Kg/l, ASTM D-1298	0,850 – 0,860
-----------------------------------	---------------

### Health and Safety:

The data related to health, safety and environmental protection are provided in the material safety data sheets.

The above figures are those relating to normal manufacturing tolerances and do not constitute a specification.

LHM Date Created: 4:=24=624& Last modification: 45=20=6248

This data sheet and the information it contains is believed to be correct with specific reference to the date of printing. The accuracy or completeness of the data and information contained in this publication are not binding in any way the responsibility of the company. The user has the obligation to evaluate and use products safely and in accordance with all applicable laws and regulations currently in force. No statement made in this publication shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a license.