



ATF DEXRON IID

REV.2 OF 03/2023

LEVELS OF QUALITY

The lubricant ATF DEXTRON IID complies with the following international specifications:

- GM DEXRON IID
- ZF TE-ML 02F, 03D, 04D, 09A, 11A, 11B, 14A, 17C
- VOITH 55.6335.32 (G607)
- MAN 339D
- ALLISON C4
- CAT TO-2
- MB 236.1-236.7
- FORD MERCON M2C 138CJ

PRODUCT DESCRIPTION

Italub ATF DEXRON IID is a lubricant recommended for automatic transmissions, power steering, hydraulically assisted steering and torque converters, whenever it is required a DEXRON II D product.

It is also used as a hydraulic oil covering a large temperature range for applications in the automotive, industry and marine field.

APPLICATIONS

It ensures excellent performances in terms of:

- frictional properties;
- thermal-oxidative stability;
- wear and corrosion resistance.

Thanks to the above mentioned features it also ensures both a low pour point and a reduced foaming tendency.

TYPICAL FEATURES*

Density at 15°C.Kg./dm ³ ASTM D1298	0.860
Colour	Red
Viscosity at 100°C.cSt ASTM D445	7.5
Viscosity Index ASTM D2270	140
Flammability V.A.°C ASTM D92	195
Pour Point °C ASTM D97	-27

*The above mentioned values are indicative of production average values and are not an integral part of the specification.