



ATF SPECIAL CVT

LEVELS OF QUALITY

The lubricant ATF SPECIAL CVT complies with the following international specifications:

- TOYOTA CVTF TC, CVTF FE
- NISSAN NS-1, NS-2
- HONDA HMMF, HCF2
- MITSUBISHI SP-III, CVTF-J1
- SUBARU ECVT, iCVT
- DAIHATSU Ammix CVT
- SUZUKI CVTF TC, NS-2, CVT Green1
- HYUNDAI SP-III
- CHRYSLER JEEP NS-2
- MB 236.20
- VW G 052 180 A2
- FORD WSS-M2C928-A
- JASO M358
- MOPAR CVTF+4
- MINI COOPER EZL799

DESCRIPTION AND APPLICATIONS

Italub ATF SPECIAL CVT is a 100% SYNTHETIC fluid of high quality, specially formulated to be used in continuously variable transmission, also called CVT. Duglas Oil ATF SPECIAL CVT is also suitable for CVT transmissions by Japanese vehicle manufacturers. In addition, it can be used for CVT Autotronic of Mercedes-Benz and CVT Multitronic of Audi.

Italub ATF SPECIAL CVT should be used if an ATF Ford M2C 166-H is required. The product is ideal for CVT functional transmissions based on van Doorne principle (Transmatic).

PROPERTIES

It ensures excellent performances in terms of:

- frictional properties;
- thermal-oxidative stability;
- wear and corrosion resistance.
- foaming resistance;
- compatibility with components for automatic transmissions, elastomer seals.
- extending oil change intervals
- more fuel efficient.

TYPICAL FEATURES*

Density at 15°C.Kg./dm ³ ASTM D1298	0.840
Colour	AMBER
Viscosity at 100°C.cSt ASTM D445	7.5
Viscosity Index ASTM D2270	165
Flammability V.A. °C ASTM D92	180
Pour Point °C ASTM D97	-39

*The above mentioned values are indicative of production average values and are not an integral part of the specification.