



## GREEN 10W

### LEVELS OF QUALITY

The lubricant GREEN 10W complies with the following international specifications:

- CAT TO-2
- ALLISON C3

### PRODUCT DESCRIPTION

Lubricants specifically developed to guarantee the maximum performance for 'Powershift' transmissions, hydraulic and axle systems and gear reducers for agricultural machineries and earthmoving equipment.

It provides good anti-wear properties, anti-stick and anti-slip properties which allow a correct effectiveness of the braking system. Furthermore, this specific formulation guarantees a reduction in power consumption and improves the efficiency of the hydraulic circuit.

### APPLICATIONS

GREEN 10W is a multifunctional product to be used on gear changes, brake transmissions and oil bath, lateral reducers, wheel reducers, differential gears, hydraulic lifts, driving pulley, mechanical and hydrostatic guide of all systems, whenever SAE 10W products are required.

### TYPICAL FEATURES\*

SAE Scale	10W
Density at 15°C.Kg./dm <sup>3</sup> ASTM D1298	0.860
Viscosity at 100°C.cSt ASTM D445	6.5
Viscosity Index ASTM D2270	135
Flammability V.A. °C ASTM D92	205
Pour Point °C ASTM D97	-24

\*The above mentioned values are indicative of production average values and are not an integral part of the specification.