



LUBRIFICANTI PER AGRICOLTURA E MOVIMENTO TERRA / FARM TRACTOR AND OFF-HIGHWAY OIL

GREEN 15W-40 S.T.O.U.



GREEN LINE

REV.2 OF 03/2023

LEVELS OF QUALITY

The lubricant GREEN 15W-40 S.T.O.U. complies with the following international specifications:

- API GL-4, CF-4
- CAT TO-2
- ALLISON C4
- John Deere J27
- Massey-Fergusson M1139

PRODUCT DESCRIPTION

A multigrade and multifunctional oil of STOU type, specifically developed for the agriculture and earthmoving fields.

The quality of basic oils along with a reliable additive package guarantee an efficient engine cleaning and protection of mechanical components against wear, even under heavy operating conditions, by providing the lubricant with:

- an excellent anti-wear capability,
- detergent and dispersant power,
- an excellent fluidity at low temperature,
- an excellent oxidation resistance.

APPLICATIONS

GREEN 15W-40 S.T.O.U. is a multifunctional product for use in all agriculture and earthmoving systems, whenever a multifunctional product is required.

The following benefits can be obtained if you use this product:

- a higher engine cleaning,
- a better protection and longer engine life,
- a good cold start,
- a good reliability under every operating conditions.

TYPICAL FEATURES*

SAE Scale	15W/40
Density at 15°C.Kg./dm3 ASTM D1298	0.870
Viscosity at 100°C.cSt ASTM D445	13.3
Viscosity Index ASTM D2270	135
Flammability V.A.°C ASTM D92	210
Pour Point °C ASTM D97	-24
T.B.N. ASTM D2896	7

*The above mentioned values are indicative of production average values and are not an integral part of the specification.