



LUBRIFICANTI PER AGRICOLTURA E MOVIMENTO TERRA / FARM TRACTOR AND OFF-HIGHWAY OIL



GREEN LINE

GREEN 80W/20W-30 U.T.T.O.

REV.2 OF 03/2023

LEVELS OF QUALITY

The lubricant GREEN 80W/20W-30 U.T.T.O. complies with the following international specifications:

- API GL-4
- ALLISON C4
- CAT TO-2
- John Deere J20C
- Massey-Ferguson M1135

PRODUCT DESCRIPTION

Multifunctional lubricant (U.T.T.O. – Universal Tractor Transmission Oil) for hydraulic transmissions and systems of earthmoving equipment and agricultural machineries in general.

It provides high anti-wear properties, anti-stick and anti-slip properties which allow the best effectiveness of the braking system. The formulation guarantees a reduction in power consumption and improves the efficiency of the hydraulic circuit.

APPLICATIONS

GREEN 80W / 20W-30 U.T.T.O. is a multifunctional product to be used on gear changes, brake transmissions and oil bath, lateral reducers, wheel reducers, differential gears, hydraulic lifts, driving pulley, mechanical and hydrostatic guide of all agricultural machineries and earthmoving equipment, whenever a product with good performance levels is required.

TYPICAL FEATURES*

SAE Scale	800W/20W-30
Density at 15°C.Kg./dm3 ASTM D1298	0.875
Viscosity at 100°C.cSt ASTM D445	10.3
Viscosity Index ASTM D2270	132
Flammability V.A. °C ASTM D92	210
Pour Point °C ASTM D97	-24

*The above mentioned values are indicative of production average values and are not an integral part of the specification.