



OLI MOTORE TRAZIONE LEGGERA / PASSENGER CAR ENGINE OILS

GT MONOGRADE 30/40/50



GT LINE
ADVANCED TECHNOLOGY
MINERAL FORMULATION

REV.2 OF 034/2023

LEVELS OF QUALITY

The lubricant GT MONOGRADE complies with the following international specifications:

- API SF, CD

DESCRIPTION

Italub GT MONOGRADE is a mono-grade, seasonal and mineral-based lubricant, designed by using selected bases and new conception additives in cars and light commercial vehicles fitted with non-turbocharged petrol and diesel engines and it can be used under light conditions.

It has been formulated with additives which reduce the formation of deposits, lacquers, and sludges both at low and high temperatures. Furthermore, it offers protection against rust, wear and corrosion and reduces the oxidation at high temperatures.

It is recommended to observe always the oil change interval as suggested by the car manufacturer.

TYPICAL FEATURES

SAE Scale	30	40	50
Density at 15°C.Kg./dm ³ ASTM D1298	0.860	0.870	0.870
Viscosity at 100°C.cSt ASTM D445	10.2	12.8	16.5
Viscosity Index ASTM D2270	130	130	130
Flammability V.A.°C ASTM D92	210	210	210
Pour Point °C ASTM D97	-18	-15	-15

The above mentioned values are indicative of production average values and are not an integral part of the specification.