



OLI MOTORE TRAZIONE LEGGERA / PASSENGER CAR ENGINE OILS

GT PLUS 15W-40



GT LINE
ADVANCED TECHNOLOGY
MINERAL FORMULATION

REV.3 OF 03/2023

LEVELS OF QUALITY

The lubricant GT PLUS 15W-40 complies with the following international specifications:

- API SL, CF
- ACEA A3/B4
- MB 229.1
- VW 501.01-505.00

DESCRIPTION

Italub GT PLUS 15W-40 is a top-quality lubricant, produced by using high-quality mineral-based oils and developed for petrol engines, but able to satisfy the requirements of new design diesel engines too. It offers a high detergent and dispersant power, an excellent resistance to corrosion and oxidation and a high antifoam power. The high viscosity index allows use under any climatic conditions (low and high external temperatures).

It provides the maximum protection for engines and guarantees the right viscosity under any operating conditions (cold starts, long distances, etc.).

It is suitable for cars fitted with a catalytic converter.

It is recommended to always observe the oil change interval as suggested by the car manufacturer.

TYPICAL FEATURES

| SAE Scale | | 15W/40 |
|-------------------------|------------|--------|
| Density at 15°C.Kg./dm3 | ASTM D1298 | 0.870 |
| Viscosity at 100°C.cSt | ASTM D445 | 13.0 |
| Viscosity Index | ASTM D2270 | 140 |
| Flammability V.A. °C | ASTM D92 | 210 |
| Pour Point °C | ASTM D97 | -24 |
| T.B.N. | ASTM D2896 | 8 |

The above mentioned values are indicative of production average values and are not an integral part of the specification.