



OLI MOTORE TRAZIONE LEGGERA / PASSENGER CAR ENGINE OILS

GT SUPREME 15W-40



GT LINE
ADVANCED TECHNOLOGY
MINERAL FORMULATION

REV.2 OF 03/2023

LEVELS OF QUALITY

The lubricant GT SUPREME 15W-40 complies with the following international specifications:

➤ API SG, SF, CD

DESCRIPTION

Italub GT SUPREME 15W-40 is a multigrade and mineral-based lubricant, designed by using carefully selected bases and new conception additives in cars and light commercial vehicles provided with non-turbocharged petrol and diesel engines.

It has been formulated with additives which reduce the formation of deposits, lacquers, and sludges both at low and high temperatures. Furthermore, it offers protection against rust, wear and corrosion and reduces the oxidation at high temperatures.

It is recommended to always observe the oil change interval as suggested by the car manufacturer.

TYPICAL FEATURES

SAE Scale	15W/40
Density at 15°C.Kg./dm ³ ASTM D1298	0.870
Viscosity at 100°C.cSt ASTM D445	13.0
Viscosity Index ASTM D2270	130
Flammability V.A.°C ASTM D92	210
Pour Point °C ASTM D97	-21
T.B.N. ASTM D2896	4.5

*The above mentioned values are indicative of production average values and are not an integral part of the specification.