



OLI MOTORE TRAZIONE LEGGERA / PASSENGER CAR ENGINE OILS



GTe LINE

100% SYNTHETIC - HYBRID TECH

GTe SKY 0W-20

REV.1 OF 03/2023

LEVELS OF QUALITY

Italub GTe SKY 0W-20 complies with the following international specifications:

- API SN PLUS
- ACEA C5

- VW 508.00/509.00
- GM dexosD
- VW TL 52 577
- PORSCHE C20
- MB 229.71
- STJLR 51.5122, 03.5006

DESCRIPTION

Italub GTe SKY 0W - 20 is a 100% SYNTHETIC lubricant specially designed for latest generation engines that must meet the Volkswagen 508.00 / 509.00 specifications strongly pushed towards the Fuel Economy and Long-Life philosophies.

In fact, Italub GTe SKY 0W - 20 boasts a very low H.T.H.S. which, combined with its Mid S.A.P.S. nature, guarantees excellent compatibility with post-treatment devices that allow the achievement of Euro VI standards.

All this is combined with great attention to achieving the highest standards of detergency, anti-wear and LSPI that complete the picture of one of the most performing lubricants in the Douglas range.

Italub GTe SKY 0W - 20 guarantees good compatibility with biofuels for all new engines.

TYPICAL FEATURES

SAE Scale		0W/20
Density at 15°C.Kg./dm ³	ASTM D1298	0.835
Colour		Blue
Viscosity at 100°C.cSt	ASTM D445	8.0
Viscosity Index	ASTM D2270	172
Flammability V.A.°C	ASTM D92	200
Pour Point °C	ASTM D97	-45
S.A.	ASTM D874	0.80
T.B.N.	ASTM D2896	8.7

*The above mentioned values are indicative of production average values and are not an integral part of the specification.