



OLI MOTORE TRAZIONE LEGGERA / PASSENGER CAR ENGINE OILS

GTe SUPER FE C5 5W-20



GTe LINE

100% SYNTHETIC - HYBRID TECH

REV.1 OF 03/2023

LEVELS OF QUALITY

Italub GTe SUPER FE C5 5W-20 complies with the following international specifications:

- API SN, CF
- API SP, SN Resource Conserving
- ACEA C5
- GM dexos1 Gen2
- ILSAC GF-5, GF-6A
- FORD WSS-M2C948-A/B, 960-A1
- STJLR 03.5004

DESCRIPTION

Italub GTe SUPER FE C5 5W - 20 is a 100% SYNTHETIC high performance engine oil developed to meet the new demands of a market that is heading towards increasingly compressed engines such as Ford EcoBoost®. The superior quality bases in combination with special additives ensure very fast lubricant distribution and optimized friction characteristics.

The very low level of HTHS denotes a marked care for the Fuel Economy. If we combine the latter with the content level of SAPS and compatibility with after-treatment systems, we obtain an extremely sensitive lubricant to emissions that fully supports the EURO VI specification. In Italub GTe SUPER FE C5 5W-20 all this is combined with careful cleaning of both deposits and sludge, with anticorrosive and anti-oxidative properties.

TYPICAL FEATURES

SAE Scale		5W/20
Density at 15°C.Kg./dm3	ASTM D1298	0.836
Viscosity at 100°C.cSt	ASTM D445	8.5
Viscosity Index	ASTM D2270	155
Flammability V.A. °C	ASTM D92	200
Pour Point °C	ASTM D97	-39
S.A.	ASTM D874	0.78
T.B.N.	ASTM D2896	8.2

The above mentioned values are indicative of production average values and are not an integral part of the specification.