



OLI MOTORE TRAZIONE LEGGERA / PASSENGER CAR ENGINE OILS

GTv ENERGY FE C1 5W-30



GTv LINE
100% SYNTHETIC

REV.4 OF 03/2023

LEVELS OF QUALITY

The lubricant GTv ENERGY FE C1 5W-30 complies with the following international specifications:

- API SN, CF
- ACEA C1
- MB 229.52
- Recommended for MAZDA, NISSAN, SUBARU
- FORD WSS M2C-934-B
- JASO DL-1
- PSA B71 2312
- JAGUAR LAND ROVER STJLR.03.5005, 51.5122

DESCRIPTION

Italub GTv ENERGY FE C1 5W-30 is a 100% synthetic lubricant with low ash content (Low SAPS) produced at the highest formulation levels, designed to provide excellent performances in modern turbocharged petrol and diesel engines complying with the new EURO V and EURO VI emission regulations.

The modern formulation technology with low ash content allows the extension of life and maintaining the efficiency of emission reduction systems of petrol and diesel cars (DPF, TWC, FAP) unchanged.

The low HTHS gives outstanding Fuel Economy (FE) properties to the lubricant, by ensuring a steady reduction in fuel consumptions.

TYPICAL FEATURES

SAE Scale		5W/30
Density at 15°C.Kg./dm3	ASTM D1298	0.850
Viscosity at 100°C.cSt	ASTM D445	11.6
Viscosity Index	ASTM D2270	150
Flammability V.A. °C	ASTM D92	210
Pour Point °C	ASTM D97	-36
S.A.	ASTM D874	0.50
T.B.N.	ASTM D2896	5

The above mentioned values are indicative of production average values and are not an integral part of the specification.