



OLI MOTORE TRAZIONE LEGGERA / PASSENGER CAR ENGINE OILS



GTv LINE
100% SYNTHETIC

GTv FLUID FE 5W-20

Rev. 3 OF 03/2023

LEVELS OF QUALITY

The lubricant GTv FLUID FE 5W-20 complies with the following international specifications:

- API SN
- ILSAC GF-5
- ACEA C2, A1/B1
- FORD WSS-M2C948-B, 948-A
- FIAT 9.55535-CR1
- BMW LL-14 FE+
- JLR STJLR 51.5122, 03.5004

DESCRIPTION

GTv FLUID FE 5W-20 is a Synthetic high-performance high-lubricity engine oil specially developed for Ford EcoBoost® series engines. The latest base fluids in combination with special additives guarantee very rapid distribution of the oil and optimized frictional properties. Unique lubricity characteristics cut fuel consumption and thus reduce emissions of pollutants.

Due to its characteristics GTv FLUID FE 5W-20 is predominantly used in Euro V and EURO VI engines where an ACEA A1/B1 engine oil is specified.

As GTv FLUID FE 5W-20 will be our basis for new engine designs good biofuel compatibility is provided.

TYPICAL FEATURES

SAE Scale		5W/20
Density at 15°C.Kg./dm3	ASTM D1298	0.840
Viscosity at 100°C.cSt	ASTM D445	8.5
Viscosity Index	ASTM D2270	155
Flammability V.A. °C	ASTM D92	200
Pour Point °C	ASTM D97	-39
S.A.	ASTM D874	0.78
T.B.N.	ASTM D2896	8.2

The above-mentioned values are indicative of production average values and are not an integral part of the specification.