



OLI MOTORE TRAZIONE LEGGERA / PASSENGER CAR ENGINE OILS

# GTv LIGHT FE C2 5W-30



**GTv LINE**  
100% SYNTHETIC

REV.6 OF 03/2023

## LEVELS OF QUALITY

The lubricant GTv LIGHT FE C2 5W-30 complies with the following international specifications:

- API SN, SM, CF
- ACEA C2, A1/B1, A5/B5
- Recommended for TOYOTA, LEXUS, NISSAN, SUBARU, HONDA, SUZUKI
- PSA B71 2290, B71 2312
- FIAT 9.55535.S1
- BMW LL-12 FE

## DESCRIPTION

Italub GTv LIGHT FE C2 5W-30 is a 100% synthetic lubricant Mid SAPS produced at the highest formulation levels, designed to provide excellent performances in modern turbocharged petrol and diesel engines complying with the new EURO V and EURO VI emission regulations.

The modern formulation technology with low ash content allows the extension of life and maintaining the efficiency of emission reduction systems of petrol and diesel cars (DPF, TWC, FAP) unchanged.

Italub GTv LIGHT FE C2 5W-30 has been specifically designed to satisfy the latest ACEA C2 specifications and is recommended for motorizations fitted with particulate filtration systems, are maintenance-free and without fuel additives.

The low HTHS gives outstanding Fuel Economy (FE) properties to the lubricant, by ensuring a steady reduction in fuel consumptions.

## TYPICAL FEATURES

SAE Scale		5W/30
Density at 15°C.Kg./dm3	ASTM D1298	0.850
Viscosity at 100°C.cSt	ASTM D445	10.3
Viscosity Index	ASTM D2270	158
Flammability V.A. °C	ASTM D92	216
Pour Point °C	ASTM D97	-36
S.A.	ASTM D874	0.80
T.B.N.	ASTM D2896	8.2

The above mentioned values are indicative of production average values and are not an integral part of the specification.