



OLI MOTORE TRAZIONE LEGGERA / PASSENGER CAR ENGINE OILS



GTv LINE
100% SYNTHETIC

GTv ULTRA 5W-30 C3 LL IV

REV.5 OF 03/2023

LEVELS OF QUALITY

The lubricant GTv ULTRA 5W-30 C3 LL IV complies with the following international specifications:

- API SN, SM, CF
- ACEA C2, C3
- MB 229.52, 229.51, 229.31, 226.51
- VW 504.00-507.00, 505.01, 506.01
- BMW LONG LIFE 04
- PORSCHE C30
- FORD WSS-M2C917-A
- FIAT 9.55535-S3

DESCRIPTION

Italub GTv ULTRA 5W-30 C3 LL IV is a LONG LIFE 100% synthetic Mid SAPS lubricant produced at the highest formulation levels, designed to provide excellent performances in modern turbocharged petrol and diesel engines complying with the new EURO V and EURO VI emission regulations. The modern formulation technology with low ash content allows the extension of life and maintaining the efficiency of emission reduction systems of petrol and diesel cars (DPF, TWC, FAP) unchanged.

Italub GTv ULTRA 5W-30 C3 LL IV has been specifically designed to satisfy the latest AUDI-Volkswagen, BMW e Mercedes-Benz specifications for motorizations with prolonged service intervals and fitted with particulate filtration systems, are maintenance-free and without fuel additives.

TYPICAL FEATURES

SAE Scale		5W/30
Density at 15°C.Kg./dm3	ASTM D1298	0.845
Viscosity at 100°C.cSt	ASTM D445	12
Viscosity Index	ASTM D2270	165
Flammability V.A.°C	ASTM D92	214
Pour Point °C	ASTM D97	-42
S.A.	ASTM D874	0.78
T.B.N.	ASTM D2896	7.2

The above-mentioned values are indicative of production average values and are not an integral part of the specification.