



GTv ULTRALIGHT FE 0W-20

REV.3 OF 03/2023

LEVELS OF QUALITY

The lubricant GTv ULTRALIGHT FE 0W-20 complies with the following international specifications:

- API SN
- ACEA C2, A1/B1
- VOLVO VCC RBSO-2AE
- FIAT 9.55535-DSX, GSX
- BMW LL-14 FE+
- ILSAC GF-5

DESCRIPTION

GTv ULTRALIGHT FE 0W-20 is a lubricant specially designed for highly stressed downsized engines with maximum power output, for extreme fuel economy characteristics and reduced CO₂ emissions. Excellent cold starting behavior, very fast oil circulation and outstanding performance reserves.

Due to its characteristics GTv ULTRALIGHT FE 0W-20 is predominantly used in Euro V and EURO VI engines where an ACEA A1/B1 engine oil is specified.

GTv ULTRALIGHT FE 0W-20 has been specially developed and approved for use in the new VOLVO VEA (Volvo Engine Architecture) engine generation.

As GTv ULTRALIGHT FE 0W-20 will be our basis for new engine designs good biofuel compatibility is provided.

TYPICAL FEATURES

SAE Scale		0W/20
Density at 15°C.Kg./dm ³	ASTM D1298	0.840
Viscosity at 100°C.cSt	ASTM D445	8.5
Viscosity Index	ASTM D2270	155
Flammability V.A. °C	ASTM D92	200
Pour Point °C	ASTM D97	-39
S.A.	ASTM D874	0.78
T.B.N.	ASTM D2896	7.5

The above mentioned values are indicative of production average values and are not an integral part of the specification.