



LEVELS OF QUALITY

The lubricant Italub OUTBOARD 4T 15W-40 complies with the following international specifications:

- API SM
- JASO MA2

DESCRIPTION

Italub OUTBOARD 4T 15W-40 is a high-performance lubricant; its formula ensures the highest levels of engine protection covering a large range of uses which are typical of outboard engines, i.e. from high-speed navigation to long operating cycles idling.

It provides reliability properties and steady performances by keeping the oil film stable, also with high levels of fuel dilution maintaining a high resistance to viscosity losses of the oil.

APPLICATIONS

Italub OUTBOARD 4T 15W-40 has been formulated for all four-stroke outboard engines for major American and Japanese manufacturers.

Its particular formulation provides:

- a reduced oil consumption and piston cleaning.
- maximum protection of the distribution system thanks to its remarkable anti-wear characteristics even at low temperatures.
- good anti-corrosion characteristics offering safe protection even during the Winter garaging.

TYPICAL FEATURES*

| SAE Scale | 15W/40 |
|--|--------|
| Density at 15°C.Kg./dm ³ ASTM D1298 | 0.875 |
| Viscosity at 100°C.cSt ASTM D445 | 14.0 |
| Viscosity Index ASTM D2270 | 135 |
| Flammability V.A.°C ASTM D92 | 220 |
| Pour Point °C ASTM D97 | -27 |
| T.B.N. ASTM D2896 | 8 |

*The above mentioned values are indicative of production average values and are not an integral part of the specification.