



PREMIUM 15W-40 S.T.O.U.

LEVELS OF QUALITY

The lubricant PREMIUM 15W-40 S.T.O.U. complies with the following international specifications:

- API CG-4, SF
- ACEA E3
- MB 228.1
- JD J27, J20C, J20D
- FORD M2C 159B, 159C, 134D
- NH 82009201, 02, 03
- CNH MAT 3525, 3526
- ZF TE-ML 06A, 06B, 07B
- MF CMD M1145, M1144, 1139, 1143, 1135

PRODUCT DESCRIPTION

A multigrade and multifunctional oil of STOU type, especially recommended for all types of agricultural diesel engines.

The quality of basic oils along with a reliable additive package guarantee an efficient engine cleaning and protection of mechanical components against wear, even under heavy operating conditions, by providing the lubricant with:

- an excellent anti-wear capability,
- detergent and dispersant power,
- an excellent fluidity at low temperature,
- an excellent oxidation resistance.

APPLICATIONS

PREMIUM 15W-40 S.T.O.U. is a multifunctional product to be used in all agriculture and earthmoving systems, whenever a product complying with newer versions of the specification is required.

The following benefits can be obtained if you use this product:

- a higher engine cleaning,
- a better protection and longer engine life,
- a good cold start.

TYPICAL FEATURES*

SAE Scale	15W/40
Density at 15°C.Kg./dm3 ASTM D1298	0.870
Viscosity at 100°C.cSt ASTM D445	13.5
Viscosity Index ASTM D2270	135
Flammability V.A.°C ASTM D92	210
Pour Point °C ASTM D97	-24
T.B.N. ASTM D2896	9

*The above mentioned values are indicative of production average values and are not an integral part of the specification.