



### LEVELS OF QUALITY

The lubricant Italub SUPER 4T 20W-50 complies with the following international specifications:

- ACEA A3
- API SM
- JASO MA, MA2

### DESCRIPTION

The lubricant Italub SUPER 4T 20W-50 is an oil produced using high quality additives. It has been designed for 4-stroke motorcycle and scooter engines cooled with water or air. It offers higher performance in terms of thermal stability, viscosimetric characteristics and fluidity at low temperatures vs. traditional oils. It provides an excellent performance for all types of 4-strokes high-powered and racing engines. It is suitable for oil bath lubrication of gears and clutches and is recommended for the use in 4-stroke small engines of generators and agricultural machineries.

### APPLICATIONS

Its specific formulation provides excellent high temperature protection under severe operating conditions and when you start a cold engine.

The following benefits can be obtained if you use this product:

- reduction in smokes coming from the exhaust pipe.
- a higher engine cleaning.
- reduced piston ring wear.

### TYPICAL FEATURES\*

SAE Scale	20W/50
Density at 15°C.Kg./dm3 ASTM D1298	0.880
Viscosity at 100°C.cSt ASTM D445	17.2
Viscosity Index ASTM D2270	140
Flammability V.A.°C ASTM D92	220
Pour Point °C ASTM D97	-21
TBN mgKOH/g ASTM D 2896	8

\*The above mentioned values are indicative of production average values and are not an integral part of the specification.