



### LEVELS OF QUALITY

The lubricant Italub SUPER 4T RACING POWER 10W-50 complies with the following international specifications:

- API SM
- JASO MA2
- Recommended for HONDA, YAMAHA, SUZUKI, KAWASAKI, DUCATI, BMW, APRILIA

### DESCRIPTION

The lubricant Italub SUPER 4T RACING POWER 10W-50 is a 100% synthetic oil produced using high quality additives. It has been designed for 4-stroke motorcycle and scooter engines cooled with water or air. It offers higher performance in terms of thermal stability, viscosimetric characteristics and fluidity at low temperatures vs. traditional oils. It provides an excellent performance for all types of 4-stroke high-powered and racing engines; it is suitable for oil bath lubrication of gears and clutches.

### APPLICATIONS

Designed to meet the needs of major manufacturers in the motorcycle field, thanks to its specific formulation provides excellent high temperature protection under severe operating conditions and when you start a cold engine.

The following benefits can be obtained if you use this product:

- reduction in smokes coming from the exhaust pipe;
- a higher engine cleaning.
- reduced piston ring wear.

### TYPICAL FEATURES

SAE Scale	10W/50
Density at 15°C. Kg./dm <sup>3</sup> ASTM D1298	0,870
Viscosity at 100°C. cSt ASTM D445	17.0
Viscosity Index ASTM D2270	155
Flammability V.A. °C ASTM D92	220
Pour Point °C ASTM D97	-27
T.B.N. ASTM D2896	8

The above mentioned values are indicative of production average values and are not an integral part of the specification