



ULTRA GEO SAE 40

LEVELS OF QUALITY

The lubricant ULTRA GEO SAE 40 complies with the following international specifications:

- API CD, CF-4, CG-4
- ACEA E2, E3
- CNG MAN 3271-1
- MB 226.9, 228.1
- RENAULT RGD
- WAUKESHA Co-Generation 7044, 7042
- DRESSER-RAND (Cat. I, II and III)

PRODUCT DESCRIPTION

A special oil for multiple applications in the field of cogeneration specifically developed for meeting the requirements of COMPRESSED NATURAL GAS (CGN) and DIESEL (HDDO) engines.

The quality of basic oils along with a reliable additive package guarantee an efficient engine cleaning and protection of mechanical components against wear, even under heavy operating conditions, by providing the lubricant with:

- an excellent anti-wear capability,
- ash control,
- high level cleaning requirements,
- an excellent oxidation resistance.

APPLICATIONS

It is a multifunctional lubricant to be used both for CGN and DIESEL engines.

It contributes to the optimization of stocks, being able to manage a single product for multiple applications

It covers distances at high levels: over 45,000 km.

TYPICAL FEATURES*

SAE Scale	40
Density at 15°C.Kg./dm ³ ASTM D1298	0,880
Density at 100°C.cSt ASTM D445	14,5
Viscosity Index ASTM D2270	125
Flammability V.A. °C ASTM D92	220
Pour Point °C ASTM D97	-24
T.B.N. ASTM D2896	8.5

*The above mentioned values are indicative of production average values and are not an integral part of the specification.